Commonwealth of Kentucky Division for Air Quality

PERMIT APPLICATION SUMMARY FORM

Completed by: Robert L. Williams

GENERAL INFORMATION:	
Name: Address: Date application received: SIC/Source description: EIS #: Application log number: AI number: Permit number:	Carmeuse Lime & Stone, Inc Black River Operation 9043 Highway 154, Butler, Kentucky 41006 December 12, 1997 3274 / Lime Production 21-191-00002 50254 3400 V-05-003
APPLICATION TYPE/PERMIT ACTIVIT	Y:
[x] Initial issuance [] Permit modification Administrative Minor Significant [] Permit renewal	[] General permit []Conditional major [x] Title V [] Synthetic minor [] Operating [x] Construction/operating
COMPLIANCE SUMMARY: [] Source is out of compliant [x] Compliance certification	
APPLICABLE REQUIREMENTS LIST: [] NSR [x] PSD [] Netted out of PSD/NSR	[x] NSPS [x] SIP [x] NESHAPS [] Other [] Not major modification per 401 KAR 51:017, 1(23)(b) or 51:052,1(14)(b)
[] Source provided terms for [x] Source subject to a MAC [] Source requested case-by [] Application proposes new [x] Certified by responsible [x] Diagrams or drawings in	y-case 112(g) or (j) determination w control technology official cluded formation (CBI) submitted in application assures

EMISSIONS SUMMARY:

Pollutant	Actual (tpy)	Potential (tpy)
PM/PM_{10}	9106.065 / 8581.074	9106.065 / 8581.074
SO_2	3334.932	3334.932
NOx	2539.086	2539.086
СО	1228.590	1228.590
VOC	0.056	0.056
LEAD	0.097	0.097
HAP \$ 10 tpy (by CAS)		
HC1	278.568	278.568

SOURCE PROCESS DESCRIPTION:

Limestone is transported from the underground mine to the surface via conveyor belts. At the surface, the limestone is crushed, washed, and conveyed to various kiln feed piles depending on the size and quality of the stone.

Limestone which is too small to be calcined in the kilns gets conveyed to aggregate piles. This stone may also be screened to produce a more closely separated product. This material may then be loaded into trucks at the site or blended and fed into truck dump hoppers which convey the stone to the limestone barge loadout.

There are five kilns at the plant. All five kilns utilize the same basic feed and counter fuel feed process. For all kilns, stone is fed directly into the kiln at a controlled rate while fuel is fed into the opposite end. As calcination takes place, the limestone is converted to quick lime. The lime is cooled and screened and either transported directly to a storage bin or screened and deposited into several bins to await shipping. Particulate emissions from the kilns are controlled by baghouses. Lime kilns #4 and #5 are equipped with continuous opacity monitors.

Lime is transported to the hydrate plant via conveyor. The lime bins at the hydrate plant feed into another bin which discharges into a weigh feeder which supplies lime to the mixer. Water is added in the mixer to produce hydrate. This material is processed and stored in silos. From the silos, it is either loaded into trucks or transported to a bagging area where it is bagged and placed on pallets.

Lime may be fed from the bins to a mill where it is pulverized. The pulverized lime is transported pneumatically to a pulverized lime storage silo. From the silo, the material is loaded into trucks.

Coal is delivered to the plant by truck and barge and stored in separate silos. Material is fed by vibrating conveyors under the silos through a conveying system, to a storage bin for each kiln. From these bins, the material is conveyed to a pulverizer to process the fuel for burning.